



Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: Security Check Paint Marker Original Yellow
- · Article number: 96669, 199013
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Industrial marker
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

LA-CO INDUSTRIES EUROPE

Allée des Combes, PI de la Plaine de l'Ain

F-01150 BLYES

**FRANCE** 

info-europe@laco.com

- · Further information obtainable from: Département sécurité du produit
- 1.4 Emergency telephone number:

24-hour emergency: CHEMTREC- U.S.: 1-800-424-9300 International: +1-703-527-3887

*Members of the public seeking specific information on poisons should contact:* 

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling: n-butyl acetate

(Contd. on page 2)





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

*Avoid breathing dust/fume/gas/mist/vapours/spray.* 

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| Dangerous | components: |
|-----------|-------------|
|           |             |

| CAS: 123-86-4 n-butyl acetate<br>EINECS: 204-658-1 | ♠ Flam. Liq. 3, H226; ♠ STOT SE 3, H336, EUH066 | 25-50% |
|--|---|--------|
|--|---|--------|

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: Store in accordance with local/regional/national/international regulations.
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.

(Contd. on page 4)





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

(Contd. of page 3)

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
Yellow
Solvent-like
Not determined.
Undetermined.

• Boiling point or initial boiling point and boiling range 124-128 °C (123-86-4 n-butyl acetate)

· Flammability Flammable.

· Lower and upper explosion limit

Lower:

 1.2 Vol % (123-86-4 n-butyl acetate)
 Upper:
 7.5 Vol % (123-86-4 n-butyl acetate)
 Flash point:
 27 °C (123-86-4 n-butyl acetate)
 Auto-ignition temperature:
 370 °C (123-86-4 n-butyl acetate)

• **Decomposition temperature:** Not determined.

(Contd. on page 5)





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

|  | (Contd. of page                              |
|--|--|
| pH   | Not determined.                              |
| Viscosity:   |  |
| Kinematic viscosity                                    | Not determined.                              |
| Kinematic viscosity                                    |  |
| Dynamic:   | Not determined.                              |
| Solubility   |  |
| water:   | Not miscible or difficult to mix.            |
| Partition coefficient n-octanol/water (log value)      | Not determined.                              |
| Vapour pressure at 20 °C:                              | 10.7 hPa (123-86-4 n-butyl acetate)          |
| Vapour pressure at 50 °C:                              | 55 hPa                                       |
| Density and/or relative density                        |  |
| Density at 20 °C:                                      | $1.84 \ g/cm^3$                              |
| Relative density                                       | Not determined.                              |
| Vapour density   | Not determined.                              |
| 9.2 Other information                                  |  |
| Appearance:  |  |
| Form:  | Pasty  |
| Important information on protection of health as       |  |
| environment, and on safety.                            | ıu   |
| Ignition temperature:                                  | Product is not selfigniting.                 |
| Explosive properties:                                  | Product is not explosive. However, formation |
| Explosive properties.                                  | explosive air/vapour mixtures are possible.  |
| Solvent content:                                       | expressive any vapour mattures are possible. |
| Organic solvents:                                      | 30.6 %                                       |
| VOC (EC)   | 30.61 %                                      |
| Solids content:  | 34.4 %                                       |
| Change in condition                                    |  |
| Evaporation rate                                       | Not determined.                              |
| <u> </u>   |  |
| Information with regard to physical hazard classes     | Void   |
| Explosives Elammable gases                             | Void<br>Void                                 |
| Flammable gases  | voia<br>Void                                 |
| Aerosols   |  |
| Oxidising gases  | Void<br>Void                                 |
| Gases under pressure                                   |  |
| Flammable liquids                                      | Flammable liquid and vapour.                 |
| Flammable solids                                       | Void<br>Void                                 |
| Self-reactive substances and mixtures                  | Void<br>Void                                 |
| Pyrophoric liquids                                     | Void<br>Void                                 |
| Pyrophoric solids Solf harding substances and mintures | Void<br>Void                                 |
| Self-heating substances and mixtures                   | Void   |
| Substances and mixtures, which emit flammable gas      |  |
| in contact with water                                  | Void   |
| Oxidising liquids                                      | Void<br>Void                                 |
| On it distincts as a list of                           |  |
| Oxidising solids Organic peroxides                     | void<br>Void                                 |

(Contd. on page 6)





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

(Contd. of page 5)

· Desensitised explosives

Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

### 123-86-4 n-butyl acetate

| Oral       | LD50     | 13,100 mg/kg (rat)    |
|------------|----------|-----------------------|
| Dermal     | LD50     | >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >21 mg/l (rat)        |

- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 7)





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

(Contd. of page 6)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| 141111 1 10 1                                     |                             |  |
|---|-----------------------------|--|
| 14.1 UN number or ID number<br>ADR, IMDG, IATA    | UN1263                      |  |
| 14.2 UN proper shipping name<br>ADR<br>IMDG, IATA | UN1263 PAINT<br>PAINT       |  |
| 14.3 Transport hazard class(es)                   | FAINI                       |  |
| •   |                             |  |
| ADR   |                             |  |
|   |                             |  |
| Class   | 3 (F1) Flammable liquids.   |  |
| Label   | 3                           |  |
| IMDG, IATA  |                             |  |
| Class   | 3 Flammable liquids.        |  |
| Label   | 3                           |  |
| 14.4 Packing group                                |                             |  |
| ADR, IMDĞ, İATÂ                                   | III                         |  |
| 14.5 Environmental hazards:                       | Not applicable.             |  |
| 14.6 Special precautions for user                 | Warning: Flammable liquids. |  |
| Hazard identification number (Kemler code):       | 30                          |  |
| EMS Number:                                       | <i>F-E,<u>S-E</u></i>       |  |
| Stowage Category                                  | A —                         |  |





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

| 14.7 Maritime transport in bulk according instruments | to IMO Not applicable.                            |
|---|---|
| Transport/Additional information:                     |   |
| ADR   |   |
| Limited quantities (LQ)                               | 5L  |
| Excepted quantities (EQ)                              | Code: E1  |
|   | Maximum net quantity per inner packaging: 30 ml   |
|   | Maximum net quantity per outer packaging: 1000 ml |
| Transport category                                    | 3   |
| Tunnel restriction code                               | D/E   |
| IMDG  |   |
| Limited quantities (LQ)                               | 5L  |
| Excepted quantities (EQ)                              | Code: E1  |
| • • • • • •   | Maximum net quantity per inner packaging: 30 ml   |
|   | Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation":                                | UN 1263 PAINT, 3, III                             |

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Service protection de l'environnement
- · Contact: Responsable QHSE
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)





Printing date 05.07.2023 Version number 7.1 (replaces version 7.0) Revision: 05.07.2023

Trade name: Security Check Paint Marker Original Yellow

(Contd. of page 8)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* \* Data compared to the previous version altered.

GB